

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets

K O P I



(11)

EP 0 860 335 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
26.08.1998 Bulletin 1998/35

(51) Int. Cl.⁶: B60R 25/02

(21) Application number: 98102886.3

(22) Date of filing: 19.02.1998

(84) Designated Contracting States:
AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC
NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 21.02.1997 US 37357 P

(71) Applicant:
HONDA GIKEN KOGYO KABUSHIKI KAISHA
Minato-ku Tokyo (JP)

(72) Inventor: Anzal, Hidehiko
Hilliard, OH 43026 (US)

(74) Representative:
Liska, Horst, Dr.-Ing. et al
Patentanwälte,
H. Weickmann, Dr. K. Fincke,
F.A. Weickmann, B. Huber,
Dr. H. Liska, Dr. J. Prechtel,
Dr. B. Böhm,
Kopernikusstrasse 9
81679 München (DE)

(54) Steering lock and ignition assembly

(57) A steering lock and ignition assembly has a two position knob for operating an ignition switch of a vehicle and for operating a steering lock mechanism of the vehicle. The knob is retained within a housing by a latch device until authorization by an authorization system is provided to the latch device. When authorization is received, the latch device releases the knob from the housing so that the steering lock mechanism can unlock the steering shaft and the ignition switch can be operated to start the vehicle.




Fig. 1

EP 0 860 335 A1

Description

BACKGROUND OF THE INVENTION

FIELD OF THE INVENTION

The present invention is directed to a steering lock and ignition assembly which can be used with a system which indirectly activates an ignition assembly such as by a user identification and authorization system. The steering lock and ignition assembly does not use a conventional mechanical key. In particular, the steering lock and ignition assembly has a two position knob for operating a conventional ignition switch and steering lock mechanism.

DESCRIPTION OF THE PRIOR ART

The prior art steering lock and ignition assemblies are well known and use a conventional mechanical key.

In this conventional key system, the user of the vehicle must carry a conventional metal key which enables him to operate the ignition switch as well as unlock other devices such as the vehicle doors, the glove box, and the trunk. If the key is lost or stolen, the user will not have access to the vehicle. If the owner's key operates all the vehicle locks, and the owner then gives his key to a third party such as a driver or valet, that person will have access to all the vehicle locks. Furthermore, if the driver gives his key to a non-driver such as a child, so that the non-driver can enter the vehicle, the non-driver can then insert the key into the ignition, start the vehicle and drive the vehicle.

Thus, the prior art systems require the carrying of a key which can be lost, misplaced or damaged. Furthermore, the prior art systems do not identify a particular person and therefore provide a level of access or authorization to the person who possesses the key.

SUMMARY OF THE INVENTION

It is a primary object of the present invention to provide a steering lock and ignition assembly which does not require a conventional metal key for operation.

It is still another object of the present invention in which the steering lock and ignition assembly has a knob which can be extended or retracted such that in the retracted position, the vehicle can not be started and the steering assembly is locked whereas in the extended position, the ignition switch can be operated and the steering assembly unlocked.

It is still another object of the present invention to provide a steering lock and ignition assembly in which the knob can be rotated relative to a housing.

It is still another object of the present invention to provide a steering lock and ignition assembly which inhibits rotation of the knob until the knob is extended.

It is still another object of the present invention to

provide a steering lock and ignition assembly having a latch for holding the knob in a retracted position.

It is still another object of the present invention to provide a steering lock and ignition assembly in which the latch includes a solenoid and a displaceable pin which releasably engages the knob.

It is still a further object of the present invention to provide a steering lock and ignition assembly which can be used with a keyless vehicle operation identification and authorization system which positively identifies the operator of the vehicle.

It is a further object of the present invention to provide a steering lock and ignition assembly which is used with a keyless vehicle operation identification and authorization system which identifies the owner or primary operator of the vehicle by means of a biometric characteristic such as a user's fingerprint, retina or voice.

The present invention is directed to a steering lock and ignition assembly comprising a housing, an ignition switch within the housing, a steering lock within the housing, a knob, and a coupling provided with the knob. The assembly is connected to the steering lock when the knob is retracted and rotated to one of at least two positions. The knob is connected to the ignition switch when the knob is extended and rotated to another one of the at least two positions. Furthermore, the coupling permits extension and retraction of the knob relative to the housing and permits rotation of the knob relative to the housing. A stop inhibits the rotation until the knob is extended.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a side view of the steering lock and ignition assembly with a knob in a retracted position.

Fig. 2 is a sectional view of the steering lock and ignition assembly with the knob in the extended position.

Fig. 3 is an end view of the knob in the extended lock position.

Fig. 4 is a simplified perspective view showing a retraction prevention feature of the present invention.

Fig. 5 is a front view showing the retraction prevention plate and the retraction tab on the ignition knob.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to Figs. 1-3, the steering lock and ignition assembly comprises a housing 5, an ignition knob 1, spring 6, solenoid 2, stopper pin 3, and indication plate 16. The ignition knob 1 is mounted on a shaft 4. The shaft 4 allows the ignition knob 1 to extend from and retract into the housing and to rotate. The shaft also interconnects the ignition knob with the ignition switch 8 and steering lock assembly 7.

In the secure position as shown in Fig. 1, the steer-

ing lock and ignition assembly is secured since the ignition knob 1 is retracted into the housing 5 so that an ignition switch 8 cannot be activated. The ignition switch 8 is conventionally known and therefore not shown in detail. The ignition knob 1 is in the LOCK position 12 such that a steering lock assembly 7 is locked and cannot be rotated. The steering lock assembly 7 is conventionally known assembly and therefore is not shown in detail. The ignition knob 1 is held in place by stopper pin 3 which is extended and inserted into recess 1a of ignition knob 1. The solenoid 2 is in a deenergized state when stopper pin 3 is extended.

When a user identification and authorization system, a remote signal transmitter or code from a keypad provides authorization for the ignition switch 8 to be activated (i.e., when the user of the vehicle has authorization to start and drive the vehicle), switch 11 is closed and power from battery 10 is applied to solenoid 2. The solenoid 2 is energized and stopper pin 3 of solenoid 2 is pulled in by a magnetic force of the solenoid (see Fig. 2). Since the stopper pin 3 no longer engages recess 1a of the ignition knob 1, the ignition knob 1 is pushed by the force of spring 6 into a projected or extended position.

Once the ignition knob 1 is extended through the indicator plate 16 by spring 6, the solenoid 2 is deenergized and the stopper pin 3 of the solenoid is moved down by the force of a spring (not shown) inside solenoid 2. Thus, with the ignition knob 1 now extended, the steering lock assembly 7 can now be unlocked and the vehicle started by activating the ignition switch 8.

In order to unlock the steering lock assembly 7, the ignition knob 1 must be rotated from the LOCK position 12 shown in Fig. 3 to the ACC position 13. Ignition knob 1 has a means which allows the ignition knob 1 to rotate passed a stop engagement member 9 from the LOCK position 12 to the ACC position 13. When the ignition knob 1 is turned from the LOCK position 12 to the ACC position 13, the steering lock assembly 7 is unlocked. Furthermore, the steering lock assembly 7 is retained in the unlocked position until the ignition knob 1 is completely pushed into the housing 5. Thus, accidental locking of the steering lock assembly 7 can be avoided. Furthermore, with the ignition knob 1 in the ACC position 13, the vehicle battery 10 is connected to the vehicle accessories to provide power thereto such as the radio, windows, etc. as in a conventional metal key system.

The steering lock assembly 7 remains in the same unlocked position when the ignition knob 1 is turned from the ACC position 13 to the ON position 14 or is turned from the ON position 14 to the START position 15. Thus, the steering lock assembly 7 remains unlocked.

The vehicle can be started by rotating the ignition knob 1 from the ACC position 13 to the START position 15 such that the ignition switch 8 is activated. After starting the vehicle, the ignition knob 1 is released by the

driver and the ignition knob 1 returns to the ON position 14 as is conventional with a metal key system. In the START position 15, the vehicle battery 10 provides power to the ignition switch 8 and start switch (not shown). In the ON position 14, the vehicle battery 10 provides power to the vehicle accessories and ignition switch 8.

When the driver of the vehicle wishes to stop and park the vehicle, the ignition knob 1 is turned counter clockwise from the ON position 14 to the ACC position 13. The steering lock assembly 7 remains in the unlocked position. The ignition knob 1 cannot be retracted into the housing 5 until a retraction tab 9 on the ignition knob 1 is aligned with the notch 30 of a retraction prevention plate 31. In the ACC, ON and START positions, the tab 9 is in abutment with the retention plate 31. The ignition knob 1 cannot be retracted until it is rotated to the LOCK position 12 where the tab 9 and the notch 30 are in alignment. Only then can the ignition knob 1 be pushed into the housing 5 flush with the face of the

indication plate 16. When the ignition knob 1 enters into the housing 5 completely, the steering lock assembly 7 finally locks the steering shaft against rotation. Furthermore, the stopper pin 3 snaps into the recess 1a of the ignition knob 1 so as to retain the ignition knob 1 within the housing 5 until the solenoid 2 is again energized.

With the steering lock and ignition assembly of the present invention, a vehicle can be started without using a conventional key which can be lost, misplaced or damaged.

While the steering lock and ignition assembly of the present invention may be activated by a signal from a remote transmitter or code from a keypad, the present invention may be used with a keyless authorization system which identifies the owner or primary operator by means of a biometric characteristic such as a user's fingerprint, retina or voice.

The present invention may be embodied in other specific forms without departing from the spirit or essential characteristics thereof. The presently disclosed embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than the foregoing description, and all changes which come within the meaning and range of equivalency of the claims are therefore to be embraced therein.

A steering lock and ignition assembly has a two position knob for operating an ignition switch of a vehicle and for operating a steering lock mechanism of the vehicle. The knob is retained within a housing by a latch device until authorization by an authorization system is provided to the latch device. When authorization is received, the latch device releases the knob from the housing so that the steering lock mechanism can unlock the steering shaft and the ignition switch can be operated to start the vehicle.

Claims

1. A steering lock and ignition assembly comprising:
 - a housing;
 - an ignition switch within said housing;
 - a steering lock within said housing;
 - a knob; and
 - a coupling providing said knob with an extended position, a retracted position, and at least two rotated positions, all relative to said housing;
 - said knob being connected to said steering lock when said knob is rotated to one of said at least two positions and said knob being connected to said ignition switch when said knob is rotated to another one of said at least two positions.
2. The steering lock and ignition assembly of claim 1, wherein said coupling includes a stop for preventing rotation of said knob when knob is in said retracted position.
3. The steering lock and ignition assembly of claim 1, further comprising:
 - a spring connected to said knob, said spring biasing said knob to extend from said housing.
4. The steering lock and ignition assembly of claim 3, further comprising:
 - a latch holding said knob flush to said housing when said knob is retracted within said housing.
5. The steering lock and ignition assembly of claim 4, wherein said latch comprises:
 - a solenoid;
 - a pin displaceable by said solenoid; and
 - a recess in said knob;
 - said pin releasably engaging said recess when said knob is in said retracted position.
6. A steering lock and ignition assembly comprising:
 - a housing;
 - a knob;
 - a coupling connecting said knob to said housing, said coupling permitting extension and retraction of said knob relative to said housing and permitting rotation of said knob relative to said housing; and
 - a stop inhibiting said rotation of said knob until said knob is extended.
7. A steering lock and ignition assembly comprising:
 - a housing;
 - an ignition means for starting a vehicle;
 - a lock means for locking a steering shaft of the vehicle;
 - movable knob means for retracting into said housing, for extending out of said housing and for rotating about an axis of said housing when extended, said movable knob means being connected to said ignition means when rotated to a first position and being connected to said lock means when rotated to a second position and retracted into said housing.
8. A steering lock and ignition assembly according to claim 7, wherein said movable knob means includes latch means for holding said movable knob means flush to said housing when retracted into said housing.
9. A steering lock and ignition assembly according to claim 7, wherein said latch means includes a solenoid, a pin displaceable by said solenoid and a recess provided in said movable knob means, wherein said pin releasably engages said recess in said movable knob means when said movable knob means is in a retracted position.
10. A steering lock and ignition assembly according to claim 8, wherein said latch means is activated by a user authorization system.
11. A steering lock and ignition assembly according to claim 7, wherein said movable knob means includes a knob and a stop for preventing said knob from rotating when retracted.
12. A steering lock and ignition assembly according to claim 7, further comprising a spring for biasing said movable knob means to extend from said housing.
13. A steering lock and ignition assembly according to claim 7, wherein said first position is a start position for starting the vehicle and said second position is a lock position for locking said lock means.
14. A steering lock and ignition assembly according to claim 13, wherein said movable knob means further rotates to an accessory position for providing power to accessories of the vehicle and for unlocking said lock means when said movable knob means is extended and rotated from the lock position.
15. A steering lock and ignition assembly according to claim 10, wherein said user authorization system is a keyless system using a biometric characteristic.




Fig. 1




Fig. 2






Fig. 3





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 10 2886

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
A	PATENT ABSTRACTS OF JAPAN vol. 6, no. 20 (M-110), 5 February 1982 & JP 56 138047 A (KOKUSAN KINZOKU KOGYO CO LTD), 28 October 1981, * abstract *	1,3,6,7	B60R25/02
A	EP 0 742 127 A (TOKAI RIKI CO LTD) 13 November 1996 * column 9, line 34 - column 13, line 20; figures 1-5 *	1,6,7	
A	PATENT ABSTRACTS OF JAPAN vol. 15, no. 509 (M-1195), 24 December 1991 & JP 03 224978 A (ALPHA CORP.), 3 October 1991, * abstract *	1,6,7	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			B60R
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 19 June 1998	Examiner Areal Calama, A-A
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/82 (P04C01)